




REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2023/02/21	ZK
S1	DRAWING UPDATES	2024/06/25	CBT




Electrical character



Detailed Product Description:
Waterproof connector rating is IP67
They can not be used permanently under water
Per ISO-20653,IEC60529


Insulation resistance: >100MΩ
Contact resistance of connector ≤10mΩ
Mechanical characteristics: mating / cycle >100cycle
Operating temperature: -25°C ~ +85°C

Contact Pin: Copper alloy with gold-plated
Insulation plastic: PA66

Cable peeling: (covering: 25mm, Conductor: 5mm)
Cable OD: 8.0~12.0mm(2 types of waterproof hoses)

ALL MATERIALS ARE RoHS COMPLIANT

Part Number	CODE	Contacts	Function	Pin ϕ (mm)	Rated voltage		Rated current	Rated impulse voltage
					A/C	D/C		
121005-01-005	L		4+FE	1.5	63V	63V	16A	1.5KV
121305-01-003	K		4+PE	1.5	630V	630V	12A	6KV
121406-01-002	M		5+PE	1.0	630V	630V	8A	6KV
120504-01-004	S		3+PE	1.5	630V	630V	12A	6KV
120503-01-002	S		2+PE	1.5	630V	630V	12A	6KV
120604-01-006	T		4	1.5	63V	63V	12A	1.5KV
121105-01-002	E		4+FE	1.5	63V	63V	16A	1.5KV
121204-01-002	F		4	1.5	63V	63V	16A	1.5KV

 Shenzhen Signal Electronics Co., LTD		TITLE M12 MALE PLASTIC ASSEMBLY CONNECTOR	
		SGN NO	SEE TABLE
DRAWN BY	DATE	DWG NO	REV.
CHECKED BY	DATE	CUSTOMER	S1
CHECKED BY	DATE	TOLERANCES ARE: DECIMALES ANGLES .x ±0.5 x.° ±2.0° .xx ±0.20 .x.° ±1.0°	
APPROVED BY	DATE		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.		THIRD ANGLE PROJECTION	
		SIZE: A4	UNITS: mm
		SCALE:	SHEET: 1 OF