

Detailed Product Description:
Waterproof connector rating is IP65/IP67
(After the connector is properly assembled Per)
ISO-20653, IEC60529



Mechanical characteristics: mating/cycle >100cycle
Operating temperature: -25°C ~ +85°C

Shell: Copper alloy with Nickel-plated

For M12 Female panel connector

ALL MATERIALS ARE RoHS COMPLIANT

④	N/A	WATERPROOF SEAL	1	PCS
③	N/A	M16 NICKEL-PLATED BRASS NUTS	1	PCS
②	N/A	WATERPROOF SEAL	1	PCS
①	N/A	M12 FEMALE BRASS MATT NICKEL PLATED FRONT LOCKING PLATE	1	PCS
ITEM	PART NO.	SPECIFICATION	Q'TY	UNIT

 SIGNAL®		TITLE	
Shenzhen Signal Electronics co.,Ltd		M12 FEMALE PANEL METAL ENCLOSURE	
DRAWN BY	DATE	SGN NO	FWK00959
CHECKED BY	DATE	DWG NO	
CHECKED BY	DATE	CUSTOMER	
APPROVED BY	DATE		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.		TOLERANCES ARE:	
		DECIMALES ANGLES	
		.x ±0.50 x.* ±2.0°	
		.xx ±0.20 .x.* ±1.0°	
		THIRD ANGLE PROJECTION	
		SIZE: A4	UNITS: mm
		SCALE: 1:1	SHEET: 1 OF 1