




REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2022/05/05	ZCH



Detailed product description:

Connector electrical character

Rating voltage: 100V AC, 140V DC,

Rating current : 2A

Insulation resistance: >1000M ohms

Contact resistance of connector ≤10m ohms

Dielectric withstanding voltage: 300V AC R.M.S.Max.

Mechanical characteristics:

Mating cycles >500 cycles


Operating temperature: -25°C ~ +85°C

Storage temperature: -10°C ~ +60°C

Cable OD: ø5.0mm

Applicable Wire: 0.15mm²(26AWG),

*All materials are RoHS compliant.



 SIGNAL® Shenzhen Signal Electronics co.,Ltd		TITLE		PUSH PULL 4PIN PLUG (SOLDER TYPE)	
		SGN NO	950104-21-001		REV.
DRAWN BY	DATE	DWG NO			
CHECKED BY	DATE	CUSTOMER			
CHECKED BY	DATE				
APPROVED BY	DATE				
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.		TOLERANCES ARE:		THIRD ANGLE PROJECTION	
		DECIMALES	ANGLES		
		.x ±0.5	x.' ±2.0°		
		.xx ±0.20	.x' ±1.0°		
		SIZE: A4	UNITS: mm		
		SCALE: 1:1	SHEET: 1 OF 1		