


SCREW LOCKING TYPE


Static Bag Packaging



Detailed Product Description:
Waterproof connector rating is IP67
They can not be used permanently under water.

Electrical character
Rating voltage: 63V AC/DC
Insulation resistance: >100MΩ
Rating current: 16A
Contact resistance: ≤5mΩ
Mechanical characteristics:
mating / cycle >500 cycle
Operating temperature: -40°C ~ +85°C

*ALL MATERIALS ARE RoHS COMPLIANT.

 SIGNAL® Shenzhen Signal Electronics Co., LTD		TITLE M12 L CODING 5 PIN(4+PE) FEMALE CONNECTOR (METAL)	
		SGN NO 121005-02-008	REV.
DRAWN BY	DATE	DWG NO	S0
CHECKED BY	DATE	CUSTOMER	
APPROVED BY	DATE	TOLERANCES ARE:	THIRD ANGLE PROJECTION
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.		DECIMALES	ANGLES
		.x ±0.5	x.* ±1.0*
		.xx ±0.2	.x.* ±0.5*
		SCALE:	SHEET: 1 OF 1