



Detailed Product Description:
Waterproof connector rating is IP67
They can not be used permanently under water
Per ISO-20653, IEC60529

Electrical character
Rating voltage: 125V AC/DC
Insulation resistance: >100MΩ
Rating current: 1.5A
Contact resistance of connector <40mΩ
Mechanical characteristics: mating cycle >100cycles
Operating temperature: -40°C ~ +105°C

ALL MATERIALS ARE RoHS COMPLIANT

P1	P2
8P8C/F	8P8C/F
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8

SIGNAL® Shenzhen Signal Electronics co.,Ltd		TITLE RJ45 8P8C/F TO RJ45 8P8C/F Adapter	
DRAWN BY	DATE	SGN NO	940008-04-006
CHECKED BY	DATE	DWG NO	
CHECKED BY	DATE	CUSTOMER	
APPROVED BY	DATE	REV.	SO
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.		TOLERANCES ARE: DECIMALES ANGLES .x ±0.3 x.* ±2.0° .xx ±0.2 .x.* ±1.0°	THIRD ANGLE PROJECTION SIZE: A4 UNITS: mm SCALE: 1:1 SHEET: 1 OF 1